

[Home](#) ■ [Обладнання](#) ■ [Обладнання для зливної каналізації](#) ■ [Мех. очищення в дощоприймачах](#) ■
[HUBER Горизонтальна решітка для переливів ROTAMAT® RoK2](#)

HUBER Горизонтальна решітка для переливів ROTAMAT® RoK2



Automatically cleaned screen for solids retention in stormwater tanks and overflows

- Efficient solids separation
- Continuous automatic screen cleaning
- Defined solids removal
- For discharges with limited upstream head possibilities
- Sturdy, low-maintenance stainless steel design

During and after storm events large amounts of debris are discharged to streams, rivers and lakes through storm water overflows of combined and sanitary sewer systems. Particularly endangered receiving water courses and nature preservation areas require more extensive measures concerning the treatment of stormwater.

The inverted upward flow storm screen ROTAMAT® RoK 2 is the ideal solution for this task, whether for new structures or refurbishment. The screen belongs to a group of fine screens designed for high flow rates at an extremely low hydraulic resistance. Twodimensional screening guarantees a very high solids retention combined with automatic, gentle cleaning of the perforated plate.

RoK 2 screens are horizontally installed before the downstream side of overflow weirs. A screw flight is mounted on a half cylinder of perforated plate. As the stormwater flows down to up through the horizontal perforated half-pipe of the screen trough the solids are retained. A screw, with a brush attached on its flights, rotates within the semi-circular screen trough. It cleans the screen and pushes the screenings gently towards the end of the trough. At the end of the trough, the screenings are returned into the sewer and carried to the wastewater treatment plant. During storm conditions the screen is automatically started and then works fully automatically.

преимущества

The screen is installed in front of the weir overflow. This design results in the following favourable benefits:

- Optimal solids retention by means of twodimensional screening (perforated plate)
- Screenings remain on the polluted water side
- No downstream impact on the screen efficiency
- For problem-free retrofitting into existing structures
- The perfect solution for discharges with limited upstream head possibilities
- Possibility of completely submerging the screen


PDF скачать

 [проспект: HUBER ROTAMAT® Storm Screen for stormwater discharges RoK 2 \(по-английски\)](#) [pdf, 371 KB]

примеры из практики

- [Recommendations for combined water screening at structures with overflow](#)
- [Optimised stormwater overflow tank functions at Kappern/Austria](#)

схема



Media



Animation: HUBER Storm Screen ROTAMAT® RoK2 for stormwater discharges with integrated weir
https://www.youtube.com/watch?v=_Rx4RVe3Si4



Animation: Screening for high water flows with HUBER screens - animation
<https://www.youtube.com/watch?v=eX4CKg7I3zw>

Інше обладнання серії Мех. очищення в дощоприймачах

- [HUBER Горизонтальна решітка для переливів ROTAMAT® RoK1](#)

Biuro Handlowe: ul. Ryżowa 51, 02-495 Warszawa, tel. + 48 22 572-28-60; fax + 48 22 572 28 68
 Serwis: ul. Ryżowa 51, 02-495 Warszawa, tel. + 48 22 572-28-60; fax + 48 22 572 28 98
 KRS: 0000132940 Organ rejestrowy: Sąd Rej. dla m.st. W-wy w Warszawie, XIII Wydział Gospod. KRS

NIP 521-009-28-15
 KRS 0000132940
 Kapitał zakładowy 500.000 zł

Member of the HUBER group:
www.huber.de